

SmartLED 3030



PRODUCT NAME

SmartLED 3030

CODE

SLBP-L-R-3060-20W-840

DESCRIPTION

SmartLED 3030 è un pannello LED professionale di MGE Lighting progettato per illuminazione diffusa e uniforme in uffici, scuole e spazi commerciali. Offre efficienza energetica, durata e qualità della luce, ideale per progetti di illuminazione LED da interno ad alta efficienza.

KEY FEATURES

- Corpo in lamiera di acciaio formato, cover in PMMA anti ingiallimento, lenti in PMMA alta trasmittente luce,, no flicker, doppio isolamento elettrico, compatibile per zone con videoterminali

TECHNICAL DATA SPECIFICATION

GENERAL INFORMATION

Lumen	2000	Light Source:	LED 2835
Power [W]:	20	Connection:	Giunto cavo
Optics:	PMMA	CCT [K°]:	4000K
Lamp body material:	Lamiera di acciaio	Color Rendering Index [CRI]	80
Optical material:	Polycarbonato	Grado IK:	5
Weight:	1	IP Rating:	40
Finish	Verniciatura a liquido bianco	Gaskets:	/

ELECTRICAL CHARACTERISTICS

Supply voltage [V AC]:	220/240	IEC protection class:	II
Power frequency [Hz]:	50/60	Power factor / COS φ :	95
Surge Common Mode [kV]:	2	Inrush current [A/ μ s]:	25

INSTALLATION

Application:	Indoor	Max Temperature [C°]:	+45
Min Temperature [C°]:	-20		

CHARACTERISTICS OF LIGHT

MacAdam:	3	Maintaining flow:	LM80B10 50.000
IPEA	/	Zero light pollution (ULR = 0%):	/

APPROVALS

Glow wire test	180	Photobiological risk:	0
CE Mark:	SI	EU RoHS Compliance:	SI

OPTIONAL

CODE	DESCRIPTION
-	-