

SmartLED 12030



PRODUCT NAME

SmartLED 12030

CODE

SLBP-IL-12030-38W-830

DESCRIPTION

SmartLED 12030 è un pannello LED professionale pensato per illuminazione diffusa e uniforme per uffici, scuole e spazi commerciali. MGE Lighting sviluppa questa soluzione per offrire efficienza energetica, durata e qualità della luce, rendendola ideale per progetti professionali di illuminazione LED da interno con pannelli ad alta efficienza.

KEY FEATURES

- Corpo in lamiera di acciaio formato, cover in PMMA anti ingiallimento, lenti in PMMA alta trasmettente luce,, no flicker, doppio isolamento elettrico, adatto per videoterminali

TECHNICAL DATA SPECIFICATION

GENERAL INFORMATION

Lumen	4000	Light Source:	SMD 2835
Power [W]:	38	Connection:	Cable joint
Optics:	PMMA	CCT [K°]:	3000
Lamp body material:	Formed steel sheet	Color Rendering Index [CRI]	80
Optical material:	PMMA	Grado IK:	4
Weight:	2Kg	IP Rating:	40
Finish	White	Gaskets:	/

ELECTRICAL CHARACTERISTICS

Supply voltage [V AC]:	200-240	IEC protection class:	II
Power frequency [Hz]:	50/60	Power factor / COS phi:	0.90
Surge Common Mode [kV]:	2	Inrush current [A/μs]:	45

INSTALLATION

Application:	Wall,Ceiling, Suspension	Max Temperature [C°]:	+45
Min Temperature [C°]:	-20		

CHARACTERISTICS OF LIGHT

MacAdam:	3	Maintaining flow:	LM80 65.000
IPEA	/	Zero light pollution (ULR = 0%):	/

APPROVALS

Glow wire test	850°	Photobiological risk:	YES
CE Mark:	YES	EU RoHS Compliance:	YES

OPTIONAL

CODE	DESCRIPTION
-	-

Polar plot

