

MiniPoint Pro



PRODUCT NAME

MiniPoint Pro

CODE

MPP-S-10W-940-24

DESCRIPTION

KEY FEATURES

- Riflettore in resina di alta qualità per un'illuminazione confortevole e senza abbagliamento
- Driver **flicker-free** per il massimo comfort visivo
- **CRI > 90** per un'eccellente resa cromatica e fedeltà dei colori
- Disponibile in diversi colori per adattarsi perfettamente all'ambiente
- Dimmerazione **DALI opzionale** e kit emergenza disponibile
- Grado di protezione **IP55** e doppio isolamento

TECHNICAL DATA SPECIFICATION

GENERAL INFORMATION

| | | | |
|---------------------|--------------------------------------|-----------------------------|-------------|
| Lumen | 1200 | Light Source: | LED COB |
| Power [W]: | 10 | Connection: | Cable joint |
| Optics: | 24° | CCT [K°]: | 4000K |
| Lamp body material: | Resin reflektor + aluminium extruded | Color Rendering Index [CRI] | 90 (min) |
| Optical material: | Resin reflektor + PC lens | Grado IK: | 55 |
| Weight: | 0,5 (Kg) | IP Rating: | IP55 |
| Finish | White | Gaskets: | / |

ELECTRICAL CHARACTERISTICS

| | | | |
|---------------------------|---------|-------------------------|------|
| Supply voltage [V AC]: | 220/240 | IEC protection class: | II |
| Power frequency [Hz]: | 50/60 | Power factor / COS phi: | 0,95 |
| Surge Common Mode [kV]: | 2 | Inrush current [A/µs]: | 30 |

INSTALLATION

| | | | |
|-----------------------|-------------------------|-----------------------|-----|
| Application: | Indoor recessed mounted | Max Temperature [C°]: | +45 |
| Min Temperature [C°]: | -20 | | |

CHARACTERISTICS OF LIGHT

| | | | |
|----------|---|----------------------------------|-------------|
| MacAdam: | 3 | Maintaining flow: | LM80 50.000 |
| IPEA | / | Zero light pollution (ULR = 0%): | / |

APPROVALS

| | | | |
|----------------|-------|-----------------------|--------|
| Glow wire test | 850°C | Photobiological risk: | Exempt |
| CE Mark: | YES | EU RoHS Compliance: | YES |

OPTIONAL

| CODE | DESCRIPTION |
|------|-------------|
| - | - |

