

MiniPoint Pro



PRODUCT NAME

MiniPoint Pro

CODE

MPP-S-10W-930-36

DESCRIPTION

KEY FEATURES

- Riflettore in resina di alta qualità per un'illuminazione confortevole e senza abbagliamento
- Driver **flicker-free** per il massimo comfort visivo
- **CRI > 90** per un'eccellente resa cromatica e fedeltà dei colori
- Disponibile in diversi colori per adattarsi perfettamente all'ambiente
- Dimmerazione **DALI opzionale** e kit emergenza disponibile
- Grado di protezione **IP55** e doppio isolamento

TECHNICAL DATA SPECIFICATION

GENERAL INFORMATION

Lumen	1200	Light Source:	LED COB
Power [W]:	10	Connection:	Cable Joint
Optics:	36°	CCT [K°]:	3000K
Lamp body material:	Resin reflektor + aluminium extruded	Color Rendering Index [CRI]	90 (Min)
Optical material:	Resin reflektor + PC lens	Grado IK:	6
Weight:	0,5 (Kg)	IP Rating:	IP55
Finish	White	Gaskets:	/

ELECTRICAL CHARACTERISTICS

Supply voltage [V AC]:	220/240	IEC protection class:	II
Power frequency [Hz]:	50/60	Power factor / COS phi:	0.95
Surge Common Mode [kV]:	2	Inrush current [A/µs]:	30

INSTALLATION

Application:	Indoor recessed mounted	Max Temperature [C°]:	-20
Min Temperature [C°]:	+45		

CHARACTERISTICS OF LIGHT

MacAdam:	3	Maintaining flow:	LM80 50.000
IPEA	/	Zero light pollution (ULR = 0%):	/

APPROVALS

Glow wire test	850°C	Photobiological risk:	Exempt
CE Mark:	YES	EU RoHS Compliance:	YES

OPTIONAL

CODE	DESCRIPTION
-	-

